




Роз'єми SAE J1453 (ORFS)

опис	тиск [бар]	номенклатура	умовний зовнішній діаметр труби				ORFS A [UN-UNF]	ORFS B [UN-UNF]
			A [мм]	A [дюйм]	B [мм]	B [дюйм]		
Редукційне пряме з'єднання  G GR	630	HO-G-09*	6	1/4	6	1/4	9/16-18	9/16-18
		HO-G-11*	8-10	5/16-3/8	8-10	5/16-3/8	11/16-16	11/16-16
		HO-G-13*	12	1/2	12	1/2	13/16-16	13/16-16
	420	HO-G-16*	14-15-16	5/8	14-15-16	5/8	1-14	1-14
		HO-G-19*	18-20	3/4	18-20	3/4	1.3/16-12	1.3/16-12
		HO-G-23*	22-25	7/8-1	22-25	7/8-1	1.7/16-12	1.7/16-12
	280	HO-G-27*	28-30-32	1.1/4	28-30-32	1.1/4	1.11/16-12	1.11/16-12
		HO-G-32*	35-38	1.1/2	35-38	1.1/2	2-12	2-12
	630	HO-GR-11-09*	8-10	5/16-3/8	6	1/4	11/16-16	9/16-18
		HO-GR-13-11*	12	1/2	8-10	3/8-5/16	13/16-16	11/16-16
	420	HO-GR-16-13*	14-15-16	5/8	12	1/2	1-14	13/16-16
		HO-GR-19-11*	18-20	3/4	8-10	3/8	1.3/16-12	11/16-16
		HO-GR-19-13*	18-20	3/4	12	1/2	1.3/16-12	13/16-16
		HO-GR-19-16*	18-20	3/4	14-15-16	5/8	1.3/16-12	1-14
		HO-GR-23-19*	22-25	7/8-1	18-20	3/4	1.7/16-12	1.3/16-12
	280	HO-GR-27-23*	28-30-32	1.1/4	22-25	7/8-1	1.11/16-12	1.7/16-12

опис	тиск [бар]	номенклатура	умовний зовнішній діаметр труби		ORFS [UN-UNF]
			[мм]	[дюйм]	
Пряме з'єднання із механізмом фіксації затискною гайкою  SV	630	HO-SV-09*	6	1/4	9/16-18
		HO-SV-11 *	8-10	5/16-3/8	11/16-16
		HO-SV-13	12	1/2	13/16-16
	420	HO-SV-16*	14-15-16	5/8	1-14
		HO-SV-19*	18-20	3/4	1.3/16-12
	280	HO-SV-23*	22-25	7/8-1	1.7/16-12
		HO-SV-27*	28-30-32	1.1/4	1.11/16-12
		HO-SV-32 *	35-38	1.1/2	2-12

опис	тиск [бар]	номенклатура	умовний зовнішній діаметр труби		[UN-UNF]
			[мм]	[дюйм]	
Гайка з різьбою UNF  MP	630	HO-MP-09*	6	1/4	9/16-18
		HO-MP-11*	8-10	5/16-3/8	11/16-16
		HO-MP-13*	12	1/2	13/16-16
	420	HO-MP-16*	14-15-16	5/8	1-14
		HO-MP-19*	18-20	3/4	1.3/16-12
		HO-MP-23*	22-25	7/8-1	1.7/16-12
	280	HO-MP-27*	28-30-32	1.1/4	1.11/16-12
		HO-MP-32*	35-38	1.1/2	2-12

* - доступні зі сталі AISI 316